

**System Contents:**

- Detached WalkAbout III®** - 5.6" LCD Display
- LLC-1.4** - Two (2) Low Light Color Camera
- AP-F3** - 3' Fixed Length Articulating Pole
- AP-T9** - 9' Telescoping/Articulating Pole
- AAM-TB** - Talkback Audio Module & Headphones
- D-BAT** - Two (2) D-Cell Battery Pack
- BAT-2** - Two (2) NiMH Rechargeable Batteries
- WBC** - Battery Charger (Power Supply not shown)
- A-CASE** - Custom Carrying Case
- WUH** - Universal Chest Harness
- SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle Power Adapter not shown

**Recommended Additions:**

- Dual Mode Thermal Camera**  
View human activity with no illumination through smoke, tear gas and dust with thermal imaging.
- Videoscope**  
Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).
- Ultra Low Light Camera**  
Infrared illumination, highly sensitive low-light BW camera.
- Baton**  
2ft. fixed length pole for access in confined spaces.
- Rescue Reel**  
Rugged reel of low signal loss cable enabling video and audio access into long vertical drops.

**SYSTEM PART NUMBERS:**

**WS-TFRST<sup>1</sup>**

**DISPLAYS**

WS=Detached WalkAbout  
 WA=Standard WalkAbout

**AUDIO**

T=AAM-TB (talkback)  
 Blank=AAM (listen-only)

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



**A-CASE**



**AP-T9**



**AP-F3**



**DETACHED WALKABOUT**



**(2) LLC-1.4**



**(2) BAT-2**



**AAM-TB**



**WBC**



**WUH**



**(2) D-BAT**

**ALTERNATE DISPLAY CONFIGURATIONS**



**STANDARD WALKABOUT**



## WalkAbout III Monitor

<b>Display Size &amp; Weight</b>	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
<b>Construction</b>	Rubber encapsulated aluminum case for shock resistance and weatherproofing
<b>Display Size</b>	5.6" (14.2cm) measured diagonally
<b>Resolution</b>	640 x 480
<b>Operating Temperature</b>	-4°F to 158°F (-20°C to 70°C)
<b>LCD Controls</b>	Brightness, contrast, color, tint, mirror, backlight & sharpness
<b>Mounting Options</b>	Display can be worn on vest, belt or harness; detached display can also be handheld
<b>Video Format</b>	Auto switches between NTSC (American) or PAL (European)
<b>Charger</b>	12VDC from either power supply or vehicle adapter
<b>Batteries</b>	NiMH, 7.2V, 2.7AH
<b>Discharge Time/ Charge Time</b>	2 hrs. with LEDs off / 2 hrs. when fully discharged
<b>Base Controls &amp; Indicators</b>	On/Off switch & LED; Camera illumination control & LED; Low battery LED;
<b>Connections</b>	Camera (pole), A/V output, DC input (7.2V to 12V)

## Camera & Audio

Model	LLC-1.4 Camera	AAM-TB Talkback Module
<b>Construction</b>	Submersible enclosure with hard-coated window	Weatherproof enclosure; fits between pole and camera
<b>Size &amp; Weight</b>	1.6"D x 2.8"L / .28 lbs (4.1 x 7.1cm / .13kg)	1.75"D x 3.5"L / 0.34 lbs. (44mmD x 89mmL / .16kg) (Less headphones)
<b>Features</b>	9 Bright white LED illuminated, color camera, 480K pixels, .15 lux, 6.0mm lens, 47° FOV	Omni-directional microphone; with hi-gain amplifier and compression circuit; switches between listen and talk mode

## Case

Model	A-CASE
<b>Construction</b>	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
<b>Size</b>	53" x 17" x 6" (135 x 43 x 15cm)
<b>Weight loaded</b>	42 lbs. (19kg)

## Poles

Model	AP-T9	AP-F3
<b>Construction</b>	3 Section telescoping pole, 2 internal aluminum sections and an external fiberglass section with foam grip	Single section fixed length fiberglass pole with foam grip
<b>Collars</b>	Rugged, break-proof, easy grip, twist collars for each pole section.	
<b>Articulation</b>	Mechanical pull cable system operated by an easy-to-use twist handle. Camera range of ± 90° with detents. Twist collar allows camera angle to be locked at any position.	
<b>Collapsed / Extended Length</b>	4ft. 3in. / 8ft. 7in. (1.3M / 2.6M)	3 ft. (.9M)
<b>Weight</b>	6.4 lbs. (2.9kg)	3.6 lbs. (1.6kg)