



PORTABLE
VIDEO
SYSTEMS

SEARCH

WalkAbout Baton System | Part #WA-CBW

System Contents:

WM-4 WalkAbout II™ - 5" LCD Display

LLC-1.4 - Low Light Color Camera

B-FNS - 2' Baton

BAT-2 - Two (2) NiMH Rechargeable Batteries

WBC - Battery Charger (Power Supply not shown)

W-CASE - Carrying Case for all other components

WUH - Universal Chest Harness

Sunshade, A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

Telescoping Pole

Extended reach with either an articulating or telescoping pole. Sizes range from 5' to 20'.

D-BAT

Allows use of alkaline 'D' cells when the rechargeable batteries are not charged. Good for emergency situations.

SYSTEM PART NUMBERS:

WA - CBW¹

DISPLAYS

WS=Detached WalkAbout
WA=Standard WalkAbout

1) Add a **"-P"** to system part number to specify a PAL (European TV standard) system.



W-CASE



B-FNS



STANDARD WALKABOUT



LLC-1.4



(2) BAT-2



WBC



WUH

ALTERNATE DISPLAY CONFIGURATIONS



DETACHED WALKABOUT



**PORTABLE
VIDEO
SYSTEMS**

Search System Specifications

WA-CBW¹

WalkAbout II Monitor

Display Size & Weight	Detached WalkAbout: 6.5"W x 7.0"H x 2.2"D / 2.1 lbs. (LCD); 5.0"W x 3.5"H x 3.5" D/2 lbs. (Base) Standard WalkAbout: 6.5"W x 9.0"H x 5.5"D / 3.65 lbs.
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing
Display Size	5 inches measured diagonally
Resolution	960 dots (H) x 234 lines (V)
Operating Temperature	-20°C to 70°C
LCD Controls	Brightness, Contrast, Color, Tint, OFF/Mirror left/right & up/down
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be hand held
Video Format	Auto switches between NTSC (American) or PAL (European)
Charger	12VDC from either power supply or vehicle adapter
Batteries	NiMH, 7.2V, 2.7AH
Discharge Time	2 hrs. with LEDs off
Charge Time	2 hrs. when fully discharged
Base Controls & Indicators	On/Off; LED intensity; Low battery
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)

Camera

Model	LLC-1.4
Construction	Submersible enclosure with hard-coated window
Size & Weight	1.6"D x 2.9"L / 0.2 lbs.
Features	9 Bright white LED illuminated, color camera, 270K pixels (320K/PAL), .03 lux, 6.0 mm, 53° FOV

Case

Model	W-CASE
Stores	WalkAbout II, camera and accessories
Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components
Size	21" x 16" x 8"
Weight loaded	17 lbs.

Pole

Model	B-FNS
Construction	Single section fixed length fiberglass pole with foam grip
Collars	None
Articulation	1 foot flexible gooseneck baton can be flexed into any position
Collapsed Length	1 ft 3 in. collapsed and folded
Extended Length	2 ft. 1 in.
Weight	1.4 lbs.