



PORTABLE
V I D E O
SYSTEMS

SEARCH

Search System | Part #WA-PSW-A9

System Contents:

WM-4 WalkAbout II™ - 5" LCD Display

LLC-1.4 - Low Light Color Camera

AP-T9 - 9' Telescoping/Articulating Pole

BAT-2 - Two (2) NiMH Rechargeable Batteries

WBC - Battery Charger (Power Supply not shown)

A-CASE - Custom Carrying Case

WUH - Universal Chest Harness

Sunshade, A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

Videoscope

Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).

Baton

2 Foot fixed length pole for access in confined spaces.

D-BAT

Allows use of alkaline 'D' cells when the rechargeable batteries are not charged. Good for emergency situations.

SYSTEM PART NUMBERS:

WA - PSW - A9¹

DISPLAYS

WS=Detached WalkAbout
WA=Standard WalkAbout

POLES

A9=9' Articulating Pole
A14=14' Articulating Pole
14=14' Gooseneck Pole

1) Add a **"-P"** to system part number to specify a PAL (European TV standard) system.



A-CASE



AP-T9



STANDARD WALKABOUT



LLC-1.4



(2) BAT-2



WBC



WUH

ALTERNATE DISPLAY CONFIGURATIONS



DETACHED WALKABOUT



**PORTABLE
VIDEO
SYSTEMS**

Search System Specifications

WA-PSW-A9' | WA-PSW-A14' | WA-PSW14'

WalkAbout II Monitor

Display Size & Weight	Detached WalkAbout: 6.5"W x 7.0"H x 2.2"D / 2.1 lbs. (LCD); 5.0"W x 3.5"H x 3.5" D/2 lbs. (Base) Standard WalkAbout: 6.5"W x 9.0"H x 5.5"D / 3.65 lbs.
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing
Display Size	5 inches measured diagonally
Resolution	960 dots (H) x 234 lines (V)
Operating Temperature	-20°C to 70°C
LCD Controls	Brightness, Contrast, Color, Tint, OFF/Mirror left/right & up/down
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be hand held
Video Format	Auto switches between NTSC (American) or PAL (European)
Charger	12VDC from either power supply or vehicle adapter
Batteries	NiMH, 7.2V, 2.7AH
Discharge Time	2 hrs. with LEDs off
Charge Time	2 hrs. when fully discharged
Base Controls & Indicators	On/Off; LED intensity; Low battery
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)

Camera

Model	LLC-1.4
Construction	Submersible enclosure with hard-coated window
Size & Weight	1.6"D x 2.9"L / 0.2 lbs.
Features	9 Bright white LED illuminated, color camera, 270K pixels (320K/PAL), .03 lux, 6.0 mm, 53° FOV

Cases

Model	Cases		
	A-CASE	T-CASE	
Part of System	WS-TSW-A9	WS-PSW-A14	WS-TSW14
Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.		
Size	53" x 17" x 6"		
Weight loaded	37 lbs.	40 lbs.	38 lbs.

Poles

Model	AP-T9	AP-T14	T-FNS-14
Part of System	WA-PSW-A9	WA-PSW-A14	WA-PSW14
Construction	3 Section telescoping pole, 2 internal aluminum sections and an external fiberglass section with foam grip	6 Section telescoping pole, 5 internal aluminum and an external fiberglass section with foam grip	4 Section fiberglass telescoping
Collars	Rugged, break-proof, easy grip, twist collars for each pole section.		
Articulation	Mechanical pull cable system operated by an easy-to-use twist handle. Camera range of ± 90° with detents. Twist collar allows camera angle to be locked at any position.		1 foot flexible gooseneck can be flexed into any position
Collapsed Length	4 ft. 3 in.	4 ft. 1 in.	4 ft with gooseneck folded
Extended Length	8 ft. 7 in.	14 ft. 1 in.	13 ft. 11 in.
Weight	6.4 lbs.	8.1 lbs.	5.3 lbs.